



LJK-600

铝幕墙接口切割锯 Notching Saw

[性能特点]

适用于铝幕墙及采光天窗型材端面特殊接口角度的加工。
配置磁栅尺控制系统，实现切割角度和工作台高度的数字显示。
工作台及定位装置调整方便，可切割出型材端面的特殊角度。
两锯片可在0°~45°范围内任意摆动。

[Product Features]

- This is the new machine type designed for the aluminum curtain-wall and lighting skylight processing with the special angle at the profile end surface.
- Equipped with magnetic ruler control system, realized Cutting Angle and worktable height digital display.
- Convenient worktable and locating device adjustment, can achieve special end surface angle processing.
- The two saw blades can swing freely at 0° ~ 45° .

④ 技术参数 Technical Parameters

电源	Power supply	380V 50Hz
电机功率	Cutting motor power	2 × 2.2kW
转速	Motor rotary speed	2800r/min
工作气压	Operation air pressure	0.5Mpa-0.8Mpa
耗气量	Air consumption	60L/min
两锯片可摆动范围	Saw blade swinging range	0° ~45°
锯切深度(垂直及水平锯片)	Cutting depth(vertical and horizontal saw blade)	210 × 150mm
进刀速度(无级调速)	Cutter feeding speed	Stepless speed regulation 0-3m/min
外形尺寸	Contour dimension(L × W × H)	3140 × 1380 × 1800mm
锯片规格	Saw Blade specification	φ 500 × φ 30 × 4.4 × 3.8 Z=120 φ 600 × φ 30 × 4.8 × 4.2 Z=144
重量	Weight	1500kg